

- **CURVATUBI 6"-24"**



HYDRAULIC SYSTEM

Type : triple gear pump SAUER DANFOSS/SALAMI/CASAPPA PLP 30 + PLP 20
Maximum oil flow : 30 lt/min
Pressure : 200 bar

CONTROLS

Type : Walvoil 3 valves $\frac{3}{4}$ " + walvoil 2 valves $\frac{1}{2}$ " for hydraulic accessories
Control : manual

ELECTRIC SYSTEM

Voltage : 12 V
Batteries : 1
Total rating : 100 Amp/hr
Alternator : 30 amperes
Starter : 4 kw

WINCH

Type : hydraulic drive
Motor : orbital type
Cable diameter: 10 mm.
Working pressure : 140bar
Speed at first layer : 4,2 mt/min

TYRES

Type : tubeless
Size : 19.0/45 R17

SPECIFICATION CYLINDER

CYLINDER	TWO OUT-BOARD	TWO IN-BOARD	ONE PIN-UP
Bore	200 mm	200 mm 150 mm	
Stroke	350 mm	180 mm 650 mm	
Stem	100 mm	70 mm	90 mm

CAPACITIES

Fuel tank	liters 100
Hydraulic system	liters 125

ENGINE

Yanmar

Model	4TNV88
Governed speed	2300 rpm
Number of cylinder	4
Bore x stroke	88 x 90
Sound	70 dB (A)